

Air-operated Waste Oil Suction


Model: S3090



- 1.The air-operated drainers air ideal for quick engine oil change by means of suction of any motor vehicle.
- 2.The transparent chamber allows the quantity and quality of sucked oil to be checked immediately.
- 3.Once depressurized,they work autonomously anywhere because they do not require continuous connection to the compressed air system.
- 4.The oil must be hot.

Model	S3090
Tank capacity	70 L
Chamber capacity	10 L
Degree of vacuum	0~negative0.08MPa
Air pressure for vacuum	8 bar
Depressurization time	2 min
Noise level	75 dB
Suction speed with oil at 70-80℃	0.6-1.6 L/min
Suction hose	1.5 m
Draining hose	1.5 m

Max.discharge pressure	1 bar
Waste liquid	Engine oil and gear oil
Net weight	26 kg



Air-operated Waste Oil Suction and Drainer

Model: S3197



1. Combination waste oil suction/drainers with transparent chamber wheel-mounted 70-litre tank equipped with level-gauge supplied with series of probes
2. The Combination waste oil suction/drainers are suitable for draining the engine oil from any motor vehicle by gravity, with vehicles placed on auto lift or pit and with probe.
3. The transparent chamber allows the quantity and quality of the sucked oil to be controlled immediately.
4. The height of collecting oil 1.65m

TECHNICAL DATA

Model	S3197
Tank capacity	70 L
Chamber capacity	10 L
Bowl capacity	10 L
Degree of vacuum	0~negative0.08MPa
Air pressure for vacuum	8 bar
Depressurization time	2 min
Noise level	75 dB

Suction speed with oil at 70-80°C	0.6-1.6 L/min
Suction hose	1.5 m
Draining hose	1.5 m
Max.discharge pressure	1 bar
Waste liquid	Engine oil and gear oil
Net weight	27 kgs

Air-operated Grease Pump

Model: S68213



Air-operated grease pump with 13 kg wheel-mounted tank.it is always ready for use and enables easy greasing at high pressure on any motor vehicle or machinery.The seamless pressed tank offers maximum guarantee of adherence and functionality of follower plate.

Technique Date

Model	S68213
Tank capacity	13kg
Length delivery hose	6m
Grease gun deliver tube	40cm
Pump delivery	63041
Compression ratio	60 : 1
Noise level	81dB
Max.working pressure	8bar
Max.air consumption	240it/min
Capacity free outlet 6 bar self-levelling grease at 20°C	1000g/min
Outside Specification	350X390X910MM

Air-operated Grease Pump

Model: S68420



Air-operated grease pump with 40 kg wheel-mounted tank.it is always ready for use and enables easy greasing at high pressure on any motor vehicle or machinery.The seamless pressed tank offers maximum guarantee of adherence and functionality of follower plate.

Technique Date

Model	68240
Tank capacity	40kg
Length delivery hose	6m
Grease gun deliver tube	40cm
Pump delivery	
Compression ratio	45 : 1
Noise level	81dB
Max.working pressure	8bar
Max.air consumption	240it/min

Capacity free outlet 6 bar self-levelling grease at 20 °C	2 l/min
Outside Specification	450X430X725MM

