

TYRE CHANGER

Model: LT410A



- With self-centering function.
- With 3-foot-operation pedals to work easier.
- Clamping system with stepping function.
- Plastic protector special for mounts/demounts tool.
- Angle of mounts/demounts tool can be adjusted and calibrated..
- Assist arm AL-340(Optional).
- Wear-resistant washer(Optional).
- Clamps for motorcycles(Optional).

•Optional colors: 

TECHNICAL DATA

Power supply/Motor power	110V/220V/380V 1.1/0.75KW	Max.Wheel diameter	39" (1000mm)
Air supply	6-10bar (0.6-1.0Mpa)	Max.Wheel width	13" (330mm)
Rim clamping range(External)	10"-22" (254mm-559mm)	Noise	<70dB
Rim clamping range(Internal)	12"-24" (305mm-610mm)	N.W./G.W.	456Lb/494Lb (207Kg/224Kg)
Bead breaker force	5500LB (2500kg)		

TYRE CHANGER

Model: LT-650



- Handles rim diameter from 14" up to 26"
- Suitable for various tires of large vehicle, applicable to tyres with gripping ring, radial ply tires, farm vehicle, passenger car, and engineering machine .
- Semi-automatic assist arm mounts/demounts the tyre more conveniently.
- Accuracy of the co-joined claw is higher.
- Mobile command unit 24V.
- Low voltage 24V remote control for safety and versatility.
- Optional colors: 

TECHNICAL DATA

Application range	Truck/bus/tractor/ industry vehicle	Clamping range	14"-26"(355-660mm)
Max.Wheel weight	1100LB (500KG)	Hydraulic pump power unit	1.5Kw 220V/380V 1PH/3PH
Max.Wheel width	30" (780mm)	Gearbox motor	1.8Kw 220V/380V 1PH/3PH
Max.Diameter of tyre	62" (1600mm)	N.W./G.W.	1287LB/1631LB (585Kg/740Kg)

TYRE CHANGER

Model: LT-910A



- Round vertical column serves as quick inflation.
- With self-centering function.
- Clamping system with stepping function.
- Angle of mount/demount tool can be adjusted and calibrated.
- The high quality polymer mounts/demounts tool prevents the rim from damage.
- Mount/demount tool with plastic protector.
- Wheel lift(Optional).

- May dispose the fluctuation cylinder simple operating system(Optional).
- Clamps for motorcycle(Optional).
- Bead seating inflation jets are integrated in the clamping jaws insuring quick and safe inflation(Optional).
- Optional colors: 

TECHNICAL DATA

Power supply/Motor power	110V/220V/380V 0.75/1.1KW	Max.Wheel diameter	43" (1100mm)
Air supply	6-10bar (0.6-1.0Mpa)	Max.Wheel width	15" (381mm)
Rim clamping range(External)	12"-26" (305-660mm)	Noise	<70db
Rim clamping range(Internal)	14"-28" (355-711mm)	N.W./G.W.	550Lb/615Lb (250Kg/279kg)
Bead breaker force	5500Lb (2500kg)		

TYRE CHANGER

Model: LT-M491



- With self-centering function.
- With 3-foot-operation pedals to work easier.
- With adjusting & calibrating functions in the 4 clamps on the turntable.
- Plastic protector special for mounts/demounts tool.
- Angle of mounts/demounts tool can be adjusted and calibrated..
- Assist arm AL-340(Optional).
- Clamping system with stepping function.
- Suitable for motorcycles.

•Optional colors: 

TECHNICAL DATA

Power supply/Motor power	110V/220V/380 1.1/0.75KW	Bead breaker force	5500Lb (2500kg)
Air supply	6-10bar (0.6-1.0Mpa)	Max.Wheel diameter	39" (1000mm)
Rim clamping range (External)first position	6"-15" (152mm-381mm)	Max.Wheel width	13" (330mm)
Rim clamping range(Internal) first position	8"-17" (203mm-432mm)	Noise	<70dB
Rim clamping range (External)second position	12"-20" (305-508mm)	N.W./G.W.	381Lb/472Lb (173kg/214kg)
Rim clamping range (Internal)second position	12"-22" (305-559mm)		